

# G+H Electrical Accessories

## Technical Datasheet

**Description:** Contour Polished Brass Unlacquered USB Charger (2x USB-C) (1 Gang/White Insert)

**Part Number:** CBUL42W



## Information

|                                |                                                                               |
|--------------------------------|-------------------------------------------------------------------------------|
| <b>Plate Dimensions (mm)</b>   | 85 (W) x 85 (H) x 8 (D)                                                       |
| <b>Insert Material</b>         | Polycarbonate                                                                 |
| <b>Earth Strap</b>             | Mild Steel                                                                    |
| <b>Operating Voltage(AC)</b>   | 250V @ 50Hz                                                                   |
| <b>Termination Type</b>        | Screw                                                                         |
| <b>Warranty</b>                | 10 years                                                                      |
| <b>Product Class 1</b>         | Must be earthed                                                               |
| <b>Maintenance</b>             | Clean with a soft cloth only. Do not use a cleaning agent of any description. |
| <b>Please Note</b>             | Do not use masking tape on this product.                                      |
| <b>Style</b>                   | Rounded Profile                                                               |
| <b>Plate Material</b>          | Solid Brass, Hand-finished, Lacquered                                         |
| <b>Required back box depth</b> | 25mm                                                                          |
| <b>Load Rating</b>             | 30W                                                                           |
| <b>Standards</b>               | BS EN 62368                                                                   |
| <b>IP Rating</b>               | IP2XD                                                                         |
| <b>Terminal Capacity</b>       | 1x2.5mm , 2x1.0mm                                                             |